

Window Tint Meter (Wireless Type)



Model: RWT-1002

Applications

Applicable to measure the transmittance of all kinds of transparent, translucent samples with parallel plane (such as automobile manufacturing, aerospace, glass products, plastic sheet, sheet, etc). Also can be used to determine the turbidity or clarity of liquid sample (water, drinks and so on).

Features

- * This Meter is a hand held device that measures the amount of light that passes through a window.
- * Technology is designed in accordance with GB 2410-80, ASTM D1033-61, JIS k7105-81 and other standards.
- * Digital display, wide range, high resolution.
- * Wireless design, easy to use.
- * One key calibration, easy to use.
- * Solid structure, small volume, light weight, easy to carry.
- * Use USB data output to connect with PC.
- * Provide Bluetooth data output choice.

Specifications

Model	RWT-1002
Display	LCD
Range	0~100%
Resolution	0.1
Accuracy	±2%
Sample Thickness	≤ 18mm / 0.7inch
Light Source	LED
Operating Conditions	Temperature: 0~50°C Humidity: < 90%
Power Supply	Main Unit: 4x1.5V AAA (UM-4) Battery Light Emitter: 2x1.5V AAA (UM-4) Battery

Size	Main Unit: 141x65x38 mm Light Emitter: 70x62x52 mm
Weight	290 g (Including Batteries)
Standard	Main Unit
Accessories	Light Emitter Testing Block Carrying Case (B04) Operation Manual
Optional Accessories	USB Data Cable with Software Bluetooth Data Adapter with Software

